

EM 235

Product Description

Product group	Emulsion	Suitable for: ✓ Aluminium ✓ Coatings ✓ Plastics/Composites
Category:	Medium Cut Compound	
Colour:	White	
Polishing wheel:	Cotton	

Menzerna EM 235 was developed especially for single-stage, robot-assisted aluminium polishing. Features outstanding heat dissipation. Very quickly creates a surface suitable for anodising, with minimum dust and dirt formation.

Process Recommendation

Surface before polishing	Super Heavy Cut	Heavy Cut	Medium Cut	Finish	Super Finish	Final surface
Aluminium	Raw part		EM 235			Suitable for anodising
	Fine throwing marks		EM 235	→	PE 25D	High gloss
	Grit size P400		EM 235		→	PE 25D

Menzerna Emulsion Programm

	Super Heavy Cut	Heavy Cut	Medium Cut	Finish	Super Finish
Aluminium	AVM 45	EM 246GD	EM 235	PE F3151	PE 25D
Brass		P 421		PE F 88	PE 25D
Stainless Steel	AVM 45	EM 246GD	PE F 86	PE F 88	PE 25D
Precious Metals					
Coatings		PE 75	PE 57E		PE R10
Plastic		PE 75	EM 235		

Container size: Hobbock, 30 Liter (20949.220.001)
Aricon TC7 Container (20949.506.001)
Container, ca. 1,2 to. (20949.515.001)

Grease content: -
Visc.: 3 – 6 Pa*s
Density: ca. 1,3 kg/l
Storage: 10°C – 30°C

Disclaimer:

All Information given in this sheet represent the best of our knowledge. Please verify before use if this product is suitable for your application.

How to find us:

Menzerna Polishing Compounds
GmbH & Co KG
Industriestrasse 25
D-76470 Ötigheim
Tel.: +49-7222-9157-0
Fax: +49-7222-9157-10
office@menzerna.com